


Ekko Series Cord-end Terminals *French Color Norm (DIN 46228)*



Standard : DIN 46228
Material : Copper (E-Cu), Tin plated
Insulation : Nylon
Operating Temperature : Maximum 105° 600 Volt




Product Code	Colour	Cross-Section mm ²	Dimensions (mm)							Package Amount	Package Weight (~gr)
			F	L	W	B	D	C			
UY-3005 E	White	0,50 mm ²	8,0	14,0	2,6	6,0	1,3	1,0	500 Pcs	64 gr.	
UY-3007 E	Blue	0,75 mm ²	8,0	14,0	2,8	6,3	1,5	1,2	500 Pcs	72 gr.	
UY-3010 E	Red	1,00 mm ²	8,0	14,0	3,0	6,3	1,7	1,4	500 Pcs	75 gr.	
UY-3015 E	Black	1,50 mm ²	8,0	14,0	3,5	6,3	2,0	1,7	500 Pcs	108 gr.	
UY-3025 E	Grey	2,50 mm ²	8,0	15,0	4,2	7,4	2,5	2,2	500 Pcs	133 gr.	
UY-3040 E	Orange	4,00 mm ²	10,0	17,0	4,8	7,4	3,2	2,8	250 Pcs	119 gr.	
UY-3060 E	Green	6,00 mm ²	12,0	20,0	6,3	8,5	3,9	3,5	250 Pcs	177 gr.	
UY-3100 E	Brown	10,00 mm ²	12,0	22,0	7,6	8,8	4,9	4,5	100 Pcs	109 gr.	
UY-3160 E	Ivory	16,00 mm ²	12,0	24,0	8,8	10,0	6,2	5,8	100 Pcs	138 gr.	
UY-3250 E	Black	25,00 mm ²	16,0	28,0	11,2	12,0	7,7	7,3	50 Pcs	125 gr.	
UY-3350 E	Red	35,00 mm ²	16,0	30,0	12,7	14,0	8,7	8,3	50 Pcs	141 gr.	
UY-3500 E	Blue	50,00 mm ²	20,0	36,0	15,0	16,0	10,9	10,3	50 Pcs	168 gr.	
UY-3700 E	Yellow	70,00 mm ²	20,0	37,0	16,0	17,0	14,3	13,5	50 Pcs	270 gr.	

Ekko Series Cord-end Terminals *German Color Norm (DIN 46228)*



Standard : DIN 46228
Material : Copper (E-Cu), Tin plated
Insulation : Nylon
Operating Temperature : Maximum 105° 600 Volt




Product Code	Colour	Cross-Section mm ²	Dimensions (mm)							Package Amount	Package Weight (~gr)
			F	L	W	B	D	C			
UY-2005 E	Orange	0,50 mm ²	8,0	14,0	2,6	6,0	1,3	1,0	500 Pcs	64 gr.	
UY-2007 E	White	0,75 mm ²	8,0	14,0	2,8	6,3	1,5	1,2	500 Pcs	72 gr.	
UY-2010 E	Yellow	1,00 mm ²	8,0	14,0	3,0	6,3	1,7	1,4	500 Pcs	75 gr.	
UY-2015 E	Red	1,50 mm ²	8,0	14,0	3,5	6,3	2,0	1,7	500 Pcs	108 gr.	
UY-2025 E	Blue	2,50 mm ²	8,0	15,0	4,2	7,4	2,5	2,2	500 Pcs	133 gr.	
UY-2040 E	Grey	4,00 mm ²	10,0	17,0	4,8	7,4	3,2	2,8	250 Pcs	119 gr.	
UY-2060 E	Black	6,00 mm ²	12,0	20,0	6,3	8,5	3,9	3,5	250 Pcs	179 gr.	
UY-2100 E	Beige	10,00 mm ²	12,0	22,0	7,6	8,8	4,9	4,5	100 Pcs	109 gr.	
UY-2160 E	Green	16,00 mm ²	12,0	24,0	8,8	10,0	6,2	5,8	100 Pcs	138 gr.	
UY-2250 E	Brown	25,00 mm ²	16,0	28,0	11,2	12,0	7,7	7,3	50 Pcs	125 gr.	
UY-2350 E	Beige	35,00 mm ²	16,0	30,0	12,7	14,0	8,7	8,3	50 Pcs	140 gr.	
UY-2500 E	Olive	50,00 mm ²	20,0	36,0	15,0	16,0	10,9	10,3	50 Pcs	168 gr.	

Ekko Series Insulated Twin Cord End Terminals (DIN 46228)



Standard : DIN 46228
Material : Copper (E-Cu), Tin plated
Insulation : Nylon
Operating Temperature : Maximum 105° 600 Volt




Product Code	Colour	Cross-Section mm ²	Dimensions (mm)						Package Amount	Package Weight (~gr)
			F	L	W	B	D	C		
UY-23005 E	White	2 x 0,50 mm ²	8,0	14,5	5,0	6,5	1,8	1,5	500 Pcs	107 gr.
UY-23007 E	Blue	2 x 0,75 mm ²	8,0	14,7	5,5	6,7	2,1	1,8	500 Pcs	121 gr.
UY-23010 E	Red	2 x 1,00 mm ²	8,0	15,1	5,5	7,1	2,4	2,1	500 Pcs	137 gr.
UY-23015 E	Black	2 x 1,50 mm ²	8,0	15,5	6,4	7,5	2,6	2,3	500 Pcs	164 gr.
UY-23025 E	Grey	2 x 2,50 mm ²	10,0	18,5	8,0	8,5	3,3	2,9	250 Pcs	137 gr.
UY-23040 E	Orange	2 x 4,00 mm ²	12,0	23,1	8,8	11,1	4,2	3,8	100 Pcs	98 gr.
UY-23060 E	Green	2 x 6,00 mm ²	14,0	26,1	9,5	12,1	5,3	4,9	100 Pcs	149 gr.
UY-23100 E	Brown	2 x 10,00 mm ²	14,0	26,6	12,6	12,6	6,9	6,5	50 Pcs	108 gr.
UY-23160 E	Beige	2 x 16,00 mm ²	14,0	31,3	19,0	17,3	8,7	8,3	50 Pcs	56 gr.

Insulated Twin Cord End Terminals (DIN 46228)



Standard : DIN 46228
Material : Copper (E-Cu), Tin plated
Insulation : Nylon
Operating Temperature : Maximum 105° 600 Volt



Product Code	Colour	Cross-Section mm ²	Dimensions (mm)						Package Amount	Package Weight (~gr)
			F	L	W	B	D	C		
UY-23005	White	2 x 0,50 mm ²	8,0	14,5	5,0	6,5	1,8	1,5	500 Pcs	107 gr.
UY-23007	Blue	2 x 0,75 mm ²	8,0	14,7	5,5	6,7	2,1	1,8	500 Pcs	121 gr.
UY-23010	Red	2 x 1,00 mm ²	8,0	15,1	5,5	7,1	2,4	2,1	500 Pcs	137 gr.
UY-23015	Black	2 x 1,50 mm ²	8,0	15,5	6,4	7,5	2,6	2,3	500 Pcs	164 gr.
UY-23025	Grey	2 x 2,50 mm ²	10,0	18,5	8,0	8,5	3,3	2,9	250 Pcs	137 gr.
UY-23040	Orange	2 x 4,00 mm ²	12,0	23,1	8,8	11,1	4,2	3,8	100 Pcs	98 gr.
UY-23060	Green	2 x 6,00 mm ²	14,0	26,1	9,5	12,1	5,3	4,9	100 Pcs	149 gr.
UY-23100	Brown	2 x 10,00 mm ²	14,0	26,6	12,6	12,6	6,9	6,5	50 Pcs	108 gr.
UY-23160	Beige	2 x 16,00 mm ²	14,0	31,3	19,0	17,3	8,7	8,3	50 Pcs	56 gr.