


## Pin Type Insulated Cable Terminals



**Material** : Copper (E-Cu), Tin plated  
**Insulation** : Nylon  
**Operating Temperature** : Maximum 105° 600 Volt




Product Code	Cross-Section mm <sup>2</sup>	Dimensions (mm)								Package Amount	Package Weight (~gr)
		W	F	L	E	D	d1	T			
<b>iK-101</b>	<b>0,50 - 1,50 mm<sup>2</sup></b>	1,9	10,0	19,8	10,0	4,0	1,7	0,75	200 Pcs	174 gr.	
<b>iK-102</b>	<b>1,50 - 2,50 mm<sup>2</sup></b>	1,9	12,0	21,8	10,0	4,5	2,3	0,80	200 Pcs	210 gr.	
<b>iK-106</b>	<b>4,00 - 6,00 mm<sup>2</sup></b>	2,8	14,0	27,0	13,0	6,4	3,4	1,00	100 Pcs	228 gr.	

## Blade Type Insulated Cable Terminals



**Material** : Copper (E-Cu), Tin plated  
**Insulation** : Vinyl  
**Operating Temperature** : Maximum 75° 600 Volt




Product Code	Cross-Section mm <sup>2</sup>	Dimensions (mm)								Package Amount	Package Weight (~gr)
		W	F	L	E	D	d1	T			
<b>iK-101/14</b>		3,0	14,0	23,8	10,0	4,0	1,7	0,75	200 Pcs	180 gr.	
<b>iK-102/18</b>		2,2	18,0	27,8	10,0	4,5	2,3	0,80	200 Pcs	206 gr.	

## Butt-splice Connectors Insulated Cable Terminals



**Standard** : DIN 46237  
**Material** : Copper (E-Cu), Tin plated  
**Insulation** : Vinyl  
**Operating Temperature** : Maximum 75° 600 Volt




Product Code	Cross-Section mm <sup>2</sup>	L	D	d1	Package Amount	PackageWeight (~gr)
<b>BY-252</b>	<b>1,50 - 2,50 mm<sup>2</sup></b>	24,6	4,5	2,3	200 Pcs	322 gr.
<b>BY-256</b>	<b>4,00 - 6,00 mm<sup>2</sup></b>	26,5	6,3	3,4	100 Pcs	285 gr.

## DIN 46230 Type Non- Insulated Cable Terminals - (Welded)



**Material** : Copper (E-Cu), Tin plated



Product Code	Cross-Section mm <sup>2</sup>	W	l1	l2	a	D	d1	h	Package Amount	PackageWeight (~gr)
<b>iK-116-13</b>	<b>16 mm<sup>2</sup></b>	22,0	38,0	18,0	21,0	13,0	2,0	2,0	100 Pcs	1,5 gr.
<b>iK-125-15</b>	<b>25 mm<sup>2</sup></b>	22,0	38,0	18,0	21,0	13,0	2,0	2,0	100 Pcs	3,7 gr.